

WEARWELL®

PREVENT. PERFORM. COMPETE.

We're dedicated to the folks that give it their all, to get the job done. We consider those hard-working men and women Industrial Athletes. Since 1950, we've designed and patented products that prevent injuries, optimize performance and position teams to compete in the toughest of all arenas - business.

Flooring

REJUVENATOR®

The ultimate ergonomic safety solution for teams in dry areas!

These large 3' x 3' (91 x 91 cm) and 1' x 3' (30 x 91 cm) modular tiles interlock on all four sides to quickly customize virtually any flooring configuration on-site.

- Polyurethane construction delivers exceptional comfort and wear
- Interlock system prevents separation
- Virtually indestructible
- Available in square or dome pattern

ERGODECK®

This versatile, ergonomic floor system will withstand heavy use in wet areas. The patented LockSafe® Positive Interlocking System delivers secure connections.

Connect any combination of ErgoDeck styles to meet the specific demands of an area.

- Customize in 3" (7.62 cm) increments
- Ability to replace single tiles reduces costs
- 100% silicone-free PVC tiles
- Wide 6" (15 cm) ramps

Matting

DIAMOND-PLATE SPONGECOTE®

A perfect combination of durability and comfort for standing workers in dry areas!

A Wearwell original, Diamond-Plate has become the matting industry's most popular surface design. However, it's what lies beneath that makes Wearwell mats outperform all others- Nitricell®. This premium nitrile rubber composite sponge is formulated for crush resistance and unmatched performance.

- Best in class performance
- Lay-flat, no-trip design
- Maximum standing area

Matting and Flooring

24/SEVEN® LockSafe®

Tired of modular mats that don't stay together? Say good bye to glue and zip-ties! Install it and forget it with our patent pending interlock system!

Available in a solid or drainage version. Use with or without edging, as individual mats or connect multiple tiles for a customized flooring solution.

Large 3' x 3' (91 x 91 cm) tiles install quickly and securely!

- Natural Rubber (GR) or Nitrile Rubber (NBR)
- Available with GRITSHIELD™ for improved traction
- Cut and connect in 12" (30 cm) increments for maximum customization

DRY CONDITIONS

WET CONDITIONS

Flooring



DRY CONDITIONS

WET CONDITIONS

Matting



Matting and Flooring

Need more information or a site-survey? We have a large team of experts that are happy to help!